



GREATNESS REINVENTED



*Details & specifications may vary according countries.

PURE DRIVING PLEASURE

Our approach to create the GR Supra was simple: we wanted to create the best driver's car.

Under the hood, is a 3.0-liter twin-scroll turbocharged with inline six redefines responsiveness, letting drivers control the throttle with millimeter precision.

To enhance the driving experience, the engine is moved as far back, and as low, as possible—optimizing the center of gravity for a 50:50 front/rear weight distribution.

The cornering stability is guaranteed by the new strut bar addition that connects the left and right strut tower which work as a mounting point from the shock breaker to create the firm handling while turning.



The exhaust manifold has been improved to bring out the Twin-scroll turbocharger's capabilities by changing it to six ports instead of the previous two.

CRUISE TO CRUSH

The straight-line stability and precise handling of the car is created by the ideal aerodynamic shape of the body and underfloor items. The aerodynamic design enables reduction of air resistance while effectively generating downforce; making it the excellent experience of driving with no hurdle.

The new Supra emblem addition on the Red Brake Caliper with prestigious design is crafted to enhance the stylish feeling to your driving moments.







SPESIFIKASI / SPECIFICATION DIMENSI & BERAT / DIMENSION & WEIGHT			GR SUPRA
			OK SOI KA
Keseluruhan / Overall	Panjang / Length	mm	4,380
	Lebar / Width	mm	1,855
	Tinggi / Height	mm	1,290
Jarak Poros Roda / Wheelbase		mm	2,470
Jarak Pijak / <i>Tread</i>	Depan / Front	mm	1,592
	Belakang / Rear	mm	1,607
MESIN / ENGINE			
Tipe Mesin / Engine Type			B58
No. of Cylinders & Arrangement			6 Cylinders, Inline Type
Mekanisme Valve / Valve Mechanisme			24-Valve DOHC, Chain Drive with Variable Valve Timing (IN/EX)
Isi Silinder / Displacement		СС	2,998
Diameter x Langkah / Bore x Stroke		mm x mm	82.0 x 94.6
Rasio Kompresi / Compression Ratio			10.2 : 1
Tenaga Mesin Maksimum / Max. Output		PS/KW/RPM	387/285/5,800-6,500
Torsi Maksimum / Max. Torque		Kgm/Nm/RPM	50.5/500/1,800-5,000
Sistem Bahan Bakar / Fuel System			Direct Injection
Turbocharger		N.	Twin-scroll Turbocharger
Transmisi / Transmission			8 AT
SASIS & SISTEM PENGGERAK / CHA	SSIS & DRIVETRAIN		
Suspensi / Suspension	Depan / Front		Double-joint Type MacPherson Strut
	Belakang / Rear	-	Multi-Link
Sistem Rem / Brake System	Depan / Front		Ventilated Disc Brake with Fixed Caliper 4-cylinder
	Belakang / Rear		Ventilated Disc Brake with Floating Caliper 1-cylinder
Harran Ban / Tira Cira	Depan / Front		255/35 R19
Ukuran Ban / Tire Size	Belakang / Rear		275/35 R19

OPSI WARNA / COLOR OPTIONS















PROMINENCE RED

LIGHTNING YELLOW

WHITE METALLIC

MATTE STORM GREY

ICE GREY METALLIC

[•] Untuk peningkatan mutu dan penyesuaian dengan perkembangan teknologi, PT Toyota Astra Motor sewaktu-waktu dapat mengubah spesifikasi, perlengkapan standar atau data lain dalam spesifikasi ini. / PT Toyota Astra Motor reserves the right to alter any details of specifications and equipments without prior notice.

[•] Spesifikasi dan kelengkapan dapat berbeda dengan gambar di brosur ini, tergantung model kendaraan. / Details and specifications may differ from the picture shown, depending on models.